

NEUTRAL TUBE QUALITY RECORDING FORM

rev 1.0

| | | | | | | | |
|----------------|--------|----------|--------|----------|--------|----------|--|
| data | | | | | | | accettab. |
| time | | | | | | | |
| | target | detected | target | detected | target | detected | |
| OD/toll | | | | | | | see tolleran. |
| WT/toll | | | | | | | |
| tube weight | | | | | | | |
| n° tube /5 kg | | | | | | | |
| sample tube | | | | | | | |
| close line | | | | | | | width max 0,1 mm lenght max 500 mm |
| total | | | | | | | |
| <2 cm | | | | | | | |
| >2<5 cm | | | | | | | |
| >5<15 cm | | | | | | | |
| >15<50 cm | | | | | | | |
| >50cm | | | | | | | |
| continue | | | | | | | |
| cm total | | | | | | | |
| thicknes | | | | | | | |
| open line | | | | | | | none |
| total | | | | | | | |
| stones | | | | | | | |
| <0,5 mm | | | | | | | |
| <1 mm | | | | | | | |
| >1 mm | | | | | | | |
| nots | | | | | | | |
| <0,5 mm | | | | | | | |
| <1 mm | | | | | | | |
| >1 mm | | | | | | | |
| cords | | | | | | | |
| rating | | | | | | | |
| shadow effetc | | | | | | | |
| rating | | | | | | | |
| Oval shaped | | | | | | | 0,4-0,8% OD |
| rating | | | | | | | |
| lopside defect | | | | | | | 6-8% OD |
| rating | | | | | | | |
| lunght | | | | | | | max + 7 mm |
| rating | | | | | | | |
| out of lineup | | | | | | | max 1,8 mm |
| rating | | | | | | | |
| bow | | | | | | | 0,9 mm su 1000 mm |
| rating | | | | | | | |
| cracks | | | | | | | none |
| n° | | | | | | | |
| lenght | | | | | | | |
| position | | | | | | | |
| skratch | | | | | | | |
| n° | | | | | | | |
| lenght | | | | | | | |
| position | | | | | | | |
| dirty | | | | | | | |
| n° | | | | | | | |
| size | | | | | | | |
| position | | | | | | | |
| glass scraps | | | | | | | see tab. |
| n° | | | | | | | |
| size | | | | | | | |
| position | | | | | | | |
| reburning | | | | | | | see tab. |
| note | | | | | | | |